

**SOUTHLAND RESOURCES, INC.
FLEETWOOD MINE, P-4004, R-3**

**SOUTHLAND RESOURCES, INC.
FLEETWOOD MINE, P-4004, R-3**

**ALABAMA SURFACE MINING COMMISSION
SURFACE MINING PERMIT APPLICATION**

PART V

Prepared By:

SIMMONS-JOHNSEY ENGINEERING, LLC
P.O. Box 1471
Jasper, Alabama 35502
Telephone (205) 275-0689 or (205) 522-2057

PART V – BONDING

A. Site Conditions (805.11)

(1) Briefly describe the site conditions within the increment which you are currently proposing to mine by answering the following:

- (a) Average premining slope: 12.3%
- (b) Percent sandstone: 53%
- (c) Final highwall slope (average): 37.0%
- (d) Acres Prime Farmland: 0
- (e) Acres Abandoned Land: 0
- (f) Average pH of topsoil substitute: 6.0

*Note: If pH range over the increment area is greater than one pH unit (units 1 through 14), give approximate number of acres which fall within each unit.

- (g) Overburden acid-base account (expressed as tons of calcium carbonate per 1,000 tons material) (only if total sulfur exceeds 0.5%: NA

B. Estimate of Reclamation Cost (780.18)

Give a detailed estimate of your cost of reclamation for the increment you are currently proposing to mine. Give individual cost estimates for grading, highwall elimination, topsoil (or topsoil substitute) replacement, revegetation and any other cost which may be applicable (prime farmland, hydrologic factors, etc.).

Bond to be determined by the ASMC.